
* EQ-5D (Quality of life).

* Last updated: 27 October 2012.

* SPSS syntax for EQ-5D sum scores.

* Source: Nederlands Tijdschrift voor Geneeskunde 2005:149(28):1574-8.

COMPUTE T0_EQ5DNL = 1.

DO IF (NVALID(T0_EQ5MO, T0_EQ5SC, T0_EQ5ACT, T0_EQ5PAIN, T0_EQ5ANX) < 5).

RECODE

T0_EQ5DNL (1 = SYSMIS).

END IF.

IF (MAX(T0_EQ5MO, T0_EQ5SC, T0_EQ5ACT, T0_EQ5PAIN, T0_EQ5ANX) > 1) T0_EQ5DNL =
T0_EQ5DNL -.071.

IF (T0_EQ5MO = 2) T0_EQ5DNL = T0_EQ5DNL - .036.

IF (T0_EQ5MO = 3) T0_EQ5DNL = T0_EQ5DNL - .161.

IF (T0_EQ5SC = 2) T0_EQ5DNL = T0_EQ5DNL - .082.

IF (T0_EQ5SC = 3) T0_EQ5DNL = T0_EQ5DNL - .152.

IF (T0_EQ5ACT = 2) T0_EQ5DNL = T0_EQ5DNL - .032.

IF (T0_EQ5ACT = 3) T0_EQ5DNL = T0_EQ5DNL - .057.

IF (T0_EQ5PAIN = 2) T0_EQ5DNL = T0_EQ5DNL - .086.

IF (T0_EQ5PAIN = 3) T0_EQ5DNL = T0_EQ5DNL - .329.

IF (T0_EQ5ANX = 2) T0_EQ5DNL = T0_EQ5DNL - .124.

IF (T0_EQ5ANX = 3) T0_EQ5DNL = T0_EQ5DNL - .325.

IF (MAX(T0_EQ5MO, T0_EQ5SC, T0_EQ5ACT, T0_EQ5PAIN, T0_EQ5ANX) > 2) T0_EQ5DNL =
T0_EQ5DNL - .234.

VARIABLE LABELS T0_EQ5DNL 'EQ-5D sumscore care receiver baseline'.

IF (missing(T0_EQ5DNL)) T0_EQ5DNL =9999.

MISSING VALUES T0_EQ5DNL (9999).

EXECUTE.