

\* Encoding: UTF-8.

\*\*\*\*\*

\* CR\_Baseline\_Quality-of-LifeEQ-5D-5L.

\* Last updated: May 31, 2018

\* SPSS syntax for EQ-5D-5L sum scores.

\* Source: Versteegh, M. M., Vermeulen, K. M., Evers, S. M., de Wit, G. A., Prenger, R., & Stolk, E. A. (2016). Dutch Tariff for the Five-Level Version of EQ-5D. Value in Health, 2016. doi:10.1016/j.jval.2016.01.003

\* Table 4, Beta, Model 3: tobit with constraints.

\*\*\*\*\*

COMPUTE T0\_EQ5D5LNL = 1.

EXECUTE.

DO IF (NVALID(T0\_EQ5MO, T0\_EQ5SC, T0\_EQ5ACT, T0\_EQ5PAIN, T0\_EQ5ANX) < 5 ).

RECODE T0\_EQ5D5LNL (1 = SYSMIS).

END IF.

IF (MAX(T0\_EQ5MO, T0\_EQ5SC, T0\_EQ5ACT, T0\_EQ5PAIN, T0\_EQ5ANX) > 1) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.047.

IF (T0\_EQ5MO = 2) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.035.

IF (T0\_EQ5MO = 3) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.057.

IF (T0\_EQ5MO = 4) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.166.

IF (T0\_EQ5MO = 5) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.203.

IF (T0\_EQ5SC = 2) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.038.

IF (T0\_EQ5SC = 3) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.061.

IF (T0\_EQ5SC = 4) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.168.

IF (T0\_EQ5SC = 5) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.168.

IF (T0\_EQ5ACT = 2) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.039.

IF (T0\_EQ5ACT = 3) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.087.

IF (T0\_EQ5ACT = 4) T0\_EQ5D5LNL = T0\_EQ5D5LNL -.192.

IF (T0\_EQ5ACT = 5) T0\_EQ5D5LNL = T0\_EQ5D5LNL - .192.

IF (T0\_EQ5PAIN = 2) T0\_EQ5D5LNL = T0\_EQ5D5LNL - .066.

IF (T0\_EQ5PAIN = 3) T0\_EQ5D5LNL = T0\_EQ5D5LNL - .092.

IF (T0\_EQ5PAIN = 4) T0\_EQ5D5LNL = T0\_EQ5D5LNL - .360.

IF (T0\_EQ5PAIN = 5) T0\_EQ5D5LNL = T0\_EQ5D5LNL - .415.

IF (T0\_EQ5ANX = 2) T0\_EQ5D5LNL = T0\_EQ5D5LNL - .070.

IF (T0\_EQ5ANX = 3) T0\_EQ5D5LNL = T0\_EQ5D5LNL - .145.

IF (T0\_EQ5ANX = 4) T0\_EQ5D5LNL = T0\_EQ5D5LNL - .356.

IF (T0\_EQ5ANX = 5) T0\_EQ5D5LNL = T0\_EQ5D5LNL - .421.

IF (missing(T0\_EQ5D5LNL)) T0\_EQ5D5LNL =9999.

EXECUTE.

VARIABLE LABELS T0\_EQ5D5LNL 'EQ-5D-5L sum score care receiver baseline'.

MISSING VALUES T0\_EQ5D5LNL (9999).